

GE 700 Plus HE

H 209

P 87

L 71

Gastronorm GN 2/1

	TN Chiller	TB Freezer	TB/TN Dual Temp	TC Heated	TC/TN Hot&Cold	N Non-refrigerated
RS - Static						
RV - Ventilated		•	•			
RS/TC S - Static and Dry Heat convertible						
RV/TC S - Ventilated / Dry Heat convertible						
HUR - Meat						
CH - Chocolate						
TC S - Dry Heat						
TC BM - Bainmarie						
N - Non-refrigerated						

Installation

Plug-in

Energy class

- A (TN)
- C (TB)

Standard equipment

- 3 white plastic coated shelves GN 2/1 (650x530 mm)
- 12 Plastic supports for GN 2/1 shelves
- 4 stainless steel racks (10 positions - pitch 130 mm)
- Door lock with key

Temperature

- -2/+8 °C (TN)
- -18/-15 °C (TB)

Refrigerant

- R600a (TN)
- R290 (TB)

Refrigeration

Ventilated

Compressor

Hermetic

Defrost

- Hot gas (TB)
- Off cycle (TN)

Climate class

5 (40 °C / 40% RH)

Opening system

- Reversible self-closing swing door
- Left or right configuration

Insulation

Cyclopentane 80 mm

Equipment handling

- Height adjustable feet (115-175H mm)
- Swivel casters with brake (optional)

External

Stainless steel AISI 304

Internal

Stainless steel AISI 304



Installazione

Plug-in

Classe Energetica

- C (TN)
- C (TB)

Dotazione di serie

- 3 Griglie plastificate bianche GN 2/1 (650x530 mm)
- 12 Supporti in plastica per griglie GN 2/1
- 4 cremagliere inox (10 posizioni - passo 130 mm)
- Serratura porta con chiave

Temperatura

- -2/+8 °C (TN)
- -18/-15 °C (TB)

Refrigerante

- R600a (TN)
- R290 (TB)

Refrigerazione

Ventilata

Compressore

Ermatico

Sbrinamento

- Gas caldo (TB)
- Fermata compressore (TN)

Classe Climatica

5 (40 °C / 40% RH)

Apertura

- Porta con ritorno automatico reversibile
- Configurazione destra o sinistra

Isolamento

Cyclopentano 80 mm

Basamento

- Piedini regolabili in altezza (115-175H mm)
- Ruote pivotanti con freno (optional)

Esterno

Acciaio inox AISI 304

Interno

Acciaio inox AISI 304