

GE 1400 Plus HE

H 209
P 87
L 144

Gastronorm GN 2/1

	TN Chiller	TB Freezer	TB/TN Dual Temp	TC Heated	TC/TN Hot&Cold	N Non-refrigerated
RS - Static						
RV - Ventilated		•	•			
RS/TC S - Static and Dry Heat convertible						
RV/TC S - Ventilated / Dry Heat convertible						
HUR - Meat						
CH - Chocolate						
TC S - Dry Heat						
TC BM - Bainmarie						
N - Non-refrigerated						



Installation

Plug-in

Energy class

- C (TN)
- C (TB)

Standard equipment

- 6 white plastic coated shelves GN 2/1 (650x530 mm)
- 6 pair of C stainless steel guide rails (652 mm) for GN 2/1 shelves/trays
- 8 stainless steel racks (20 positions - pitch 130 mm)
- Door lock with key

Temperature

- -2/+8 °C (TN)
- -18/-15 °C (TB)

Refrigerant

R290

Refrigeration

Ventilated
Compressor
Hermetic

Defrost

- Hot gas (TB)
- Off cycle (TN)

Climate class

5 (40 °C / 40% RH)

Opening system

- Reversible self-closing swing door
- Left or right configuration

Insulation

Cyclopentane 80 mm

Equipment handling

- Height adjustable feet (115-175H mm)
- Swivel casters with brake (optional)

External

Stainless steel AISI 304

Internal

Stainless steel AISI 304

Optionals

- Swivel casters with brake
- GN 2/1 white plastic coated/stainless steel shelves (650x530 mm)
- EN 60x40 white plastic coated/stainless steel shelves (600x400 mm)
- White plastic coated/stainless steel central shelves (540x216 mm)
- GN 2/1 stainless steel trays (650x530x20/40/60/100H mm)
- EN 60x40 stainless steel trays (600x400x20H mm)
- C stainless steel guide rails pair (652 mm) for GN 2/1 shelves/trays
- 2L stainless steel guide rails pair (652 mm) for EN 60x40-GN 2/1 shelves/trays
- Kit 4 stainless steel racks maximum load (42 positions - pitch 60mm)
- White plastic coated basket (650x530x150/300H mm)

Installazione

Plug-in

Classe Energetica

- C (TN)
- C (TB)

Dotazione di serie

- 6 Griglie GN 2/1 plastificate bianche (650x530 mm)
- 6 Coppie guide C (652 mm) per griglie/teglie GN 2/1
- 8 cremagliere inox (20 posizioni - passo 130 mm)
- Serratura porta con chiave

Temperatura

- -2/+8 °C (TN)
- -18/-15 °C (TB)

Refrigerante

R290

Refrigerazione

Ventilata

Compressore

Ermetico

Sbrinamento

- Gas caldo (TB)
- Fermata compressore (TN)

Classe Climatica

5 (40 °C / 40% RH)

Apertura

- Porta con ritorno automatico reversibile
- Configurazione destra o sinistra

Isolamento

Cyclopentano 80 mm

Basamento

- Piedini regolabili in altezza (115-175H mm)
- Ruote pivotanti con freno (optional)

Esterno

Acciaio inox AISI 304

Interno

Acciaio inox AISI 304

Accessori

- Ruote pivotanti con freno
- Griglie GN 2/1 plastificate bianche / inox (650x530 mm)
- Griglie EN 60x40 plastificate bianche / inox (600x400 mm)
- Griglie centrali plastificate bianche/ inox (540x216 mm)
- Teglie GN 2/1 inox (650x530x20/40/60/100H mm)
- Teglie inox EN 60x40 (600x400x20H mm)
- Coppia guide C inox (652 mm) per griglie/teglie GN 2/1
- Coppie guida 2L inox (652 mm) per griglie/teglie EN 60x40-GN 2/1
- Kit 4 cremagliere massimo carico (42 posizioni - passo 60mm)
- Cesto plastificato bianco (650x530x150/300H mm)

